

PRODUCT CHART



Decorative coating

Secoia®

Reference	Characteristics	Bio based content	Positionning & Use
Secoia® 1400	Short oil alkyd emulsion	95% minimum	Low color single binder for wall paint

Inokem® / Inokem® UR

Reference	Characteristics	Bio based content	Positionning & Use
Inokem® 1101	Short oil alkyd emulsion with low VOC	53% maximum	Conventional alkyd emulsion Low Cost & low color; used alone or as co-binder (20/30% in blend)
Inokem® 1105	Short oil alkyd emulsion	53% maximum	Self crosslinking single binder for interior wall paint based on Leaf Tech® technology)
Inokem® UR 3301	Short oil alkyd Urethane dispersion	53% maximum	Conventiional hybrid resins for single use or in blend with acrylics/styrene acrylics for bathroom or kitchen paints

Wood coatings

Secoia®

Reference	Characteristics	Bio based content	Positionning & Use
Secoia® 4400	Short oil surfactant-free alkyd emulsion	96% minimum	Single binder for indoor coatings based on Pickering technology
Secoia® 4487	Long oil alkyd emulsion	99% minimum	Binder for deep impregnation; excellent penetration and protection based on Pickering technology

Inokem® UR

Reference	Characteristics	Bio based content	Positionning & Use
Inokem® UR 3301	Short oil alkyd Urethane dispersion	53% maximum	Conventional & versatile hybrid resin for indoor/outdoor coatings
Inokem® UR 3304	Short oil alkyd Urethane dispersion	50% maximum	Colorless hybrid resin for Top Coat indoor/outdoor coatings
Inokem® UR 3308	Medium oil alkyd Urethane dispersion	69% maximum	Penetrating hybrid resin for primer or impregnation
Inokem® UR 3309	Short oil alkyd Urethane dispersion	50% maximum	High hardness colorless hybrid resin for indoor/outdoor coatings

Metal coatings

Inokem® UR

Reference	Characteristics	Bio based content	Positionning & Use
Inokem® UR 3301	Short oil alkyd Urethane dispersion	53% maximum	Conventional & versatile hybrid resin for indoor/outdoor coatings
Inokem® UR 3304	Short oil alkyd Urethane dispersion	50% maximum	Colorless hybrid resin for Top Coat indoor/outdoor coatings
Inokem® UR 3309	Short oil alkyd Urethane dispersion	50% maximum	High hardness colorless hybrid resin for indoor/outdoor coatings

More information available on request. Please contact : info@ecoat.fr